

Wireless Remote High-Temperature Sensor with Stainless Steel Cable and Probe - 116

Part Number: SS3-116

Overview

Swift Sensors Wireless Remote High-Temperature Sensor with Stainless Steel Cable and Probe with 1m (3") meshed steel lead and a 15cm (6") food grade stainless steel conical probe measures temperatures up to 300°C (572°F). The sensor enclosure is water-resistant and dustproof with a rating of IP66. When a detection event occurs, notifications can be sent via SMS text, email, and phone call.

Simple, Plug-and-Play Deployment

Place the small battery-powered sensor in the location or on the equipment you need to monitor. The Swift Sensors Gateway instantly identifies the sensor and establishes secure communication. No wires to connect. No software to install. Sensors are powered with 2 AAA lithium polymer batteries with an average lifespan of 6 - 8 years. Sensors can be powered on or put into sleep mode by pressing the center of the sensor. A green LED in the sensor blinks when the sensor powers on, turns solid when transitioning to sleep mode, and will blink when the "Find my Sensor" command is sent from the Console. All sensors send encrypted data to the gateway.

Secure, Scalable, Cloud Architecture

The system is 100% cloud-managed. The gateway securely transmits sensor data to the Swift Sensors Cloud using 256-bit AES encryption. The system is scalable from a single sensor, one site application to multi-site enterprises with thousands of sensors.

Real-time Monitoring and Analytics with Actionable Data

Swift Sensors Console allows real-time asset monitoring and sophisticated analysis from anywhere – on a computer, tablet, or smartphone. Data analytics provide operational insights and deep visibility. SMS text, email, and phone call notifications can be set based on customizable threshold values and complex rules by individual sensors or sensor groups.


Applications

- ✓ Agriculture and Greenhouse Monitoring
- ✓ Facilities Management
- ✓ Food Manufacturing
- ✓ Hospitality
- ✓ Restaurants
- ✓ Greenhouses
- ✓ School Districts and Universities
- ✓ Cold Chain Monitoring
- ✓ Transportation
- ✓ Building Management

Operational Specifications:

Power	1.8 - 3.6VDC, 0.05mW Average
Battery Type	AAA x2 Replaceable "L92" Lithium Polymer
Operating Voltage	1.8VDC - 3.6VDC
Avg. Current Consumption	18uA (Active), 500uA (Command ACK), <5uA(Sleep)
Operating Temperature	-40°C to +60°C (-40°F to +140°F) Defined by Batteries
Operating Environment	Indoor/Outdoor, 0-95%+ RH
Battery Life (Average)	6 - 8 Years
Communication Protocol	BLE/BT5 2.4Ghz
BLE Chipset	nRF52840
TX Strength	Default +8dBm
Range	70m - 90m (250ft - 300ft) Line-of-Sight 30m - 45m (100ft - 150ft) Non Line-of-Sight
Encryption	128-Bit AES Encryption
Button Press	Click to turn on. Press and Hold 2 sec to put in sleep mode
LED	Green LED: 2 sec. blinking when turning on Green LED: 2 sec. solid when entering sleep mode
Find My Sensor	Command from Console to blink sensor LED
Weight	84g (3 oz)
Dimensions	77.5mm x 57.5mm x 44mm (2.26in. x 1.73in. x 0.73in.)
Enclosure Material	ABS PA-765+
IP Rating	IP66
Cable Specifications	1.2 Meters Long (47") Stainless-Steel Braiding for Harsh Environmental Protection
Right-Angle Probe Dimensions	0.15 Meters (6") of Straight Probe Length 5mm (0.197") Probe Diameter 27.94mm (1.1") Bent Length, 40.64mm (1.6") Bend Depth Right-Angle Orientation; Penetrating Tip

Operational Specifications Cont.:

Certifications 	FCC ID: X8WBT840F IC ID: 4100A-BT840F CE Compliance: 2014/35/EU, 2014/53/EU, 2014/30/EU
EMC Compliance	FCC Part 15 Class B
Flammability Rating	UL94-0V
Warranty	2-years

Measurements Specs:

General Use Indications	Monitoring the Measurements of Higher Temperatures in Harsh, Dry Environments Indoors or Outdoors
Measurement Range	-30°C to +300°C (-22°F to +572°F)
Resolution	14-Bit
Accuracy	0.25C-0.3C, High-Sensitivity to Transient Air Temp.
Precision	Up to 0.001C
Inspection Rate	1 - 30 Minutes (Default 5 Minutes)

Swift Sensors Gateway

The Swift Sensors Gateway collects encrypted data from sensors located within the specified communication range (< 90m/300ft) and then transmits the sensor data to the Swift Sensors Cloud through either Ethernet, Wi-Fi, or cellular. The gateway auto-detects all sensors within range and will immediately establish secure communication without any user configuration or setup. Each gateway can support up to 150 Series 3 sensors.

Swift Sensors Console

All sensor data is logged and stored in the Swift Sensors Cloud. The Swift Sensors Console is configured to monitor and track all sensor data in the cloud. Multiple thresholds and alerts can be set separately for each sensor to supply notification via SMS text, email, or phone call. The console can be viewed in a web browser on a computer, tablet, or smartphone.

No programming is required to configure the console. An API to the Swift Sensors Platform allows integration with other data sources and 3rd-party data analytics tools.